

Air-Operated Hydraulic Stud Tensioner Pump Options

Specification	CTP-100	HTP-100	HTP-200
<i>Input Air Flow (ft³/min, m³/min):</i>	28 (0.79)	28 (0.79)	56 (1.6)
<i>Output Flow Rates (in³/min):</i>			
<i>5,000 psi Output Pressure *1:</i>	15	15	37
<i>15,000 psi Output Pressure *1:</i>	12	12	28
<i>30,000 psi Output Pressure *1:</i>	6	6	16
<i>Output Flow Rates (ml/min):</i>			
<i>500 Bar Output Pressure *2:</i>	230	230	600
<i>1,500 Bar Output Pressure *2:</i>	160	160	380
<i>2,000 Bar Output Pressure *2:</i>	110	110	300
<i>Hydraulic Reservoir Capacity (gal/l):</i>	1.0 (3.6)	1.0 (3.6)	1.8 (6.8)
<i>Overall Weight with Oil (lb/kg):</i>	53 (24)	69 (31)	81 (37)
<i>Dimensions (in, cm):</i>			
<i>Width:</i>	21 (53)	19 (48)	19 (48)
<i>Height:</i>	9 (23)	24 (61)	30 (76)
<i>Depth:</i>	17 (43)	19 (49)	19 (49)

Notes:

1. With an 80 psi input air supply.
1. With an 5.5 Bar input air supply.



CTP-100 Compact, Air-Operated Hydraulic Pump. Lock & ship via UPS or FedEx.

HTP-100 Air-Operated Hydraulic Stud Tensioner Pump.