


B-RAD SELECT

**NEW! Now with digital torque settings.
Torque ranges up to 4,000 Nm!**

The newly designed B-RAD Select offers unmatched power, versatility, and reliability while incorporating a new torque display with buttons. The B-RAD Select allows the user to easily select the target torque. Patented Product.

- Now with digital torque settings, able to increase or decrease the value by 10 ft. lbs.
- Torque ranges up to 3,000 ft. lbs.
- Equipped with the latest lithium-ion technology
- Suitable for pre-torque and service jobs where electricity or compressed air are not available



PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (FT.)		RPM	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
			LOW	HIGH						
24501	B-RAD SELECT 500	0.75"	125	500	13	7.6	9.25"	2.5"	2.65"	10.25"
24502	B-RAD SELECT 500-2	0.75"	150	500	58	9.2	11.25"	2.5"	2.65"	10.25"
24503	B-RAD SELECT 1000	0.75"	200	1000	6	8.2	10.00"	2.5"	2.65"	10.25"
24504	B-RAD SELECT 1000-2	0.75"	200	1000	20	10	11.88"	2.5"	2.65"	10.25"
24505	B-RAD SELECT 1500	1.0"	300	1500	9.2	8.9	9.75"	2.7"	2.7"	10.25"
24506	B-RAD SELECT 1500-2	1.0"	300	1500	18	10.7	13.00"	2.7"	2.7"	10.25"
24281	B-RAD SELECT 3000	1.0"	600	3000	2	13	11.00"	3.2"	3.2"	10.25"
24928	B-RAD SELECT 3000-2	1.0"	600	3000	13	16.2	13.25"	3.2"	3.2"	10.25"

Accuracy of +/-5%, Repeatability of +/-2%

RAD TORQUE SYSTEMS